

origin

DOORS AND WINDOWS

A woman with long brown hair, wearing a grey textured cardigan and dark trousers, stands in a large bi-fold door. She is looking out at a lush garden with green trees and a stone wall. The door is partially open, and the view outside is bright and clear. The floor inside is light-colored wood.

Origin Bi-fold Doors

Operating Instructions

Opening the doors

1. Insert the key into the lock on the lead door, turn it 360° to unlock the door and remove.
2. Open the now unlocked door and fold it back onto the magnetic keep on the adjacent door.
3. To open the remaining doors, **A rotate** the slave handle(s) 180° to release the shoot bolts.
4. For doors opening out, **B push** the door frame above the D-handle and **C** guide the doors open fully, ensuring that the lead door remains against its magnet at all times.

For doors opening in, gently pull on the slave handle to start the doors in motion. Once away from the tracks, release the handle and guide them to the fully open position using the opposite side of the door which is closest to the tracks.



Systems with a lead door

Closing the doors

1. Place your hand between the two doors closest to the wall and **A guide** along the track.*
2. For doors opening out, **B pull** the D-handle to close the doors. Lock them into place by **C rotating** the slave handle(s) 180°.

For even door sets opening in, gently pull on the finger pull handle to start the doors in motion. Once on the tracks and shut, release the handle and lock the doors into place by rotating the slave handle(s) 180°. Follow all other steps in order to ensure your doors are fully secure after closing.

3. Repeat the previous steps until all slave handles are in the locked position.
4. Using the lead door handle, pull the door from the magnetic keep and close.
5. Lift the handle up to engage the locks.
6. Insert the key into the lock, rotate it 360° to lock and remove.



Opening the doors

1. If keyed locking is installed, insert the key into the lock, turn it 360° and remove.
2. Rotate all slave handles 180° (90° if keyed locking installed).
3. For doors opening out, push the door frame above the slave handle and guide open the doors fully.

For doors opening in, gently pull on the slave handle to start the doors in motion. Once away from the tracks, release the handle and guide them to the fully open position using the opposite side of the door which is closest to the tracks.



Systems without a lead door

Helpful hints and tips:

Always remove the key from the lock to prevent damage occurring to the lock and adjacent doors.

The lead door is always the first door to open and the last to close.

The lead door must remain attached to the magnetic keep when the doors are open and in operation.

Neither the slave handle or lever handles should be used to pull the doors along the track or into the closed position.

Closing the doors

1. For doors opening out, place your hand between the two doors closest to the wall and guide the doors along the track.*

For doors opening in, push the frame until the doors are closed.



2. Once closed, lock the doors into place by rotating the slave handle(s) 180° (90° if keyed locking installed).

3. Repeat the previous steps until all slave handles are in the locked position.

4. If keyed locking is installed, insert the key, rotate 360° and remove.



Origin accept no warranty claims for damage caused by keys being left in the locks or for slave handles being misused.

*Please note, the door restrictor (on odd sets, French doors and single doors only) restricts the door from opening beyond the optimum opening point and is not to be used as a permanent solution to prevent the door from closing. DO NOT USE IN WINDY CONDITIONS.

origin

If you would like any aspect of the door operation explaining to you,
please call or email a member of the team using the details below.

t 0808 168 5816 e enquiry@origin-global.com w www.origin-global.com

